



UTTERMOST

## ASSEMBLY AND INSTALLATION INSTRUCTIONS

21302

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

### Installation Steps

- Carefully unpack your new fixture and lay out all the parts on a clear surface.
- Slip center hole of Metal ring-1 over nipple-3, then secure with the Finial.
- Hook the Crystal cluster-A and Crystal cluster-B to the Main body. ( Hang A and B alternately)
- Slip center hole of Cap over nipple-2, then secure with the Loop.
- Hook the Decorative cable (Short) to the Cap and Metal ring-1.
- Slip the Ring over the Decorative cable (Long) and hook Decorative cable (Long) to the Metal ring-1 and Metal ring-2.
- Thread Hex nut-2 onto Nipple-1, insert Lock washer over the end of Nipple-1, thread Nipple-1 through Mounting bar and secure with Hex nut-1 continue until tight.
- Thread Green ground screw into the hole near the two dimples of Mounting bar. Secure Mounting bar to outlet box with Outlet box screws.
- Weave Fixture Wire and Ground Wire through Chain links. Open Quick link-2, connect Loop to one end link of Chain and close Quick link-2.
- Thread Collar ring to Collar loop, secure Collar loop to Nipple-1 through Canopy. Open Quick link-1, connect Collar loop to the other one link of Chain and close Quick link-1.
- Make Wire connections with Wire Connector:
  - The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
  - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.
 Carefully tuck wires back into the Outlet box.
- After wires are connected, place the Canopy on the ceiling and secure Collar ring. Then tuck them carefully inside outlet box.
- Install the light Halogen bulbs (Supplied) are include and 40W wattage, G9 and 4pcs. In accordance with the fixture's specifications.
 

**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
- Turn on the power at fuse or Circuit Box.

