

# UTTERMOST

## ASSEMBLY INSTRUCTIONS

21388

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

*We suggest a licensed electrician for all fixture installations*

### Installation Steps

1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
2. Attached the mounting bar to outlet box with outlet box screws, Thread nipple into mounting bar and secure with lock washer and hex nut, Do not thread nipple less than three turns.
3. If needed, Assemble the stems together using the nipple, then attach the bottom end of stem onto the Coupling tightly, then secure the Swivel onto the top end of the stem.
4. Assemble the swivel onto the canopy and secure with steel washer, washer & hex nut tightly. adjust wire length needed for install, remove excess.
5. Make Wire connections with Wire Connector:
  - The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - The ribbed wire (w/o marking) from Fixture To White Wire from power source.
  - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw. Carefully tuck wires back into the Outlet Box.
6. Attach the canopy over the outlet box and let the nipple protrude through the mounting hole of the canopy, then secure with hex nut & ball nut.
7. Put the fabric shade onto the Socket, and secure with the Socket ring.
8. Assemble the acrylic tail into the wheel.
9. Install the light bulb in accordance with the fixture's specifications.  
**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
10. Turn on the power at fuse or Circuit Box.

