


UTTERMOST LIGHTING ASSEMBLY INSTRUCTIONS

ITEM # : 22421

**IMPORTANT : TURN OFF THE POWER AT THE MAIN FUSE
OR CIRCUIT BREAKER BOX
BEFORE STARTING INSTALLATION**

Carefully unpack and identify all parts before assembly.

1. Be sure the power to the installation point is off.
2. Pull the power supply wires out from the outlet box, and mount the universal mounting plate to the outlet box, using mounting screws A.
3. Attach the power supply wires to the fixture lead wires by connecting black to black, and white to white. Attach the power supply ground wire from the outlet box and the fixture ground wire from the fixture to the green ground screw on the mounting bracket or connect both wires together using the correct size of wire connectors.
4. Install the back plate over the screw B and secure with ball finial.
5. Install glass shade and candle onto fitters by fastening counter rings onto threaded sockets.
6. Install bulbs (no included). See relamping label located at socket area for type and maximum allowed wattage.



UTTERMOST LIGHTING INSTALLATION INSTRUCTIONS:

FOR WALL MOUNT (FIG. 1)

1. BEFORE INSTALLING FIXTURE, CAREFULLY UNPACK AND IDENTIFY ALL PARTS REFERRING TO ILLUSTRATION FIGURE 1. BE SURE THE POWER TO THE INSTALLATION POINT IS OFF.

1. PLACE THE #8-32 HEX NUTS ONTO THE #8-32 FIXTURE MOUNTING SCREWS, AND ATTACH THE FIXTURE MOUNTING SCREWS TO THE MOUNTING BRACKET OR UNIVERSAL MOUNTING PLATE.

2. PULL THE POWER SUPPLY WIRES OUT FROM THE OUTLET BOX, AND MOUNT THE MOUNTING BRACKET OR THE UNIVERSAL MOUNTING PLATE TO THE OUTLET BOX, USING MOUNTING SCREWS.

3. ATTACH THE POWER SUPPLY WIRES TO THE FIXTURE LEAD WIRES BY CONNECTING BLACK TO BLACK AND WHITE TO WHITE. ATTACH THE POWER SUPPLY GROUND WIRE FROM THE OUTLET BOX AND THE FIXTURE GROUND WIRE FROM THE FIXTURE TO THE GREEN GROUND SCREW ON THE MOUNTING BRACKET OR CONNECT BOTH WIRES TOGETHER USING THE CORRECT SIZE OF WIRE CONNECTORS.

FIGURE 1.

