

# UTTERMOST

## ASSEMBLY INSTRUCTIONS

**STYLE#: 22523**

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

*Carefully unpack all lamp parts from carton. We suggest a licensed electrician for all fixture installations.*

1. Take the lamp carefully out of the Carton, and place on a flat surface.
2. Be sure power to the installation point is OFF.
3. Pull the power supply wire out from the outlet box and mount the **Universal Bar** to the outlet box with **Mounting Screws**.
4. Connect the wire as shown.
  - a. Connect the House Ground Wire to the Fixture Ground Wire, secure with wire nut.
  - b. Connect the House White (or Ribbed) Wire to the Fixture Supply Wire (White or Ribbed Side), secure with wire nut.
  - c. Connect the House Black (or Red) Wire to the Fixture Supply Wire (Black or Smooth Side), secure with wire nut.
  - d. Carefully stuff all of the connected wires into the Outlet Box.
5. Place the **Backplate** over the **Mounting Screws** and secure with **Mounting Balls**. Hand-tighten until snug.
6. Slide **Glass Shade** over socket and thread **Metal Sleeve #1** then **Metal Sleeve #2** onto **Socket**. Then use **Plastic Wrench** to lock the **Socket Collar** onto the socket to secure the **Glass Shade**. Tighten until snug.
8. Install the correct **Bulb** (Not Included) into the **Socket** until snug.

**Your installation is completed now. Restore electricity.**

