

UTTERMOST

ASSEMBLY INSTRUCTIONS

STYLE#: 22531

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Carefully unpack all lamp parts from carton. We suggest a licensed electrician for all fixture installations.

1. Be sure the power to the installation point is off.
2. Pull the power supply wires out from the outlet box, and mount the **Universal Bar** to the outlet box with **Outlet Box Screws**.
3. Attach the power supply wires to the fixture lead wires by connecting black to black, and white to white. Attach the power supply ground wire from the outlet box and the fixture ground wire from the fixture to the green ground screw on the mounting bracket or connect both wires together using the correct size of wire connectors.
4. Align the Holes in the **Blackplate** with the **Mounting Screws** attached to the **Universal Bar**.
5. Pass the fixture over the **Mounting Screws** and secure again by threading **Mounting Balls** onto end of Screw. Tighten until snug.
6. Place the **Fabric Shade** carefully onto the **Socket**.
7. Install the **Bulb** referring to fixture markings and/or labels for maximum wattage on the **Socket** (No Included)

Your installation is completed now. Restore electricity

