UTTERMOST ASSEMBLY INSTRUCTIONS

22870 22871

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF WHILE POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

We suggest a licensed professional electrician for installation

Installation Steps

- 1. Turn power off at fuse or circuit box before starting installation process.
- 2. Carefully unpack your new fixture and lay out all the parts on a clear surface.
- Position the Mounting plate through the fixing holes onto the wall and make marks, drill pilot holes for Wood screws into the wall, then insert the Plastic anchor into the holes.
- 4. Secure Mounting plate to Outlet box with Outlet box screws, then secure the outlet box with wood screws into Plastic anchors in the wall.
- Make Wire connections with Wire Connector:
 ---The smooth wire (w/ marking) from fixture to Black Wire from power source.

---The ribbed wire (w/o marking) from Fixture to White Wire from power source.

---Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.

Carefully tuck wires back into the Outlet Box.

- 6. Mount the Back plate over the Mounting plate and then secure it with Mounting screws.
- 7. Slide the bottom Glass into the Glass holder, then secure with the Plastic washer and Finial.
- 8. Install the light bulbs (Not Supplied) in accordance with the fixture's specifications.
- 9. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
- 10. Slip the Glass over the socket and into the Glass holder.

