
















# UTTERMOST


## ASSEMBLY INSTRUCTIONS

ITEM: 23884


PARTS LIST							
NO	DRAWING	PARTS NAME	Q'TY	NO	PARTS NAME	DRAWING	Q'TY
A		FLAT WASHER 5/16"*3/4"	8PCS	1	SEAT FRAME		1PC
B		LOCK WASHER 5/16"	8PCS	2	RIGHT FRONT LEG		1PC
C		BOLTS DIA 5/16"*1-3/4"	4PCS	3	LEFT FRONT LEG		1PC
D		BOLTS DIA 5/16"*2-1/4"	4PCS	4	RIGHT BACK LEG		1PC
E		ALLEN WRENCH 5/16"	1PC	5	LEFT BACK LEG		1PC
F		WOOD SCREW 2"	8PCS	6	LEFT SIDE STRETCHER		1PC
				7	RIGHT SIDE STRETCHER		1PC
				8	FRONT STRETCHER		1PC
				9			1PC

ASSEMBLY BOLTS MAY NEED TIGHTEND AFTER USE

### STEP 1



### STEP 2



NOTE : Leave BOLTS loose by 1/4 turn when securing LEGS until after STEP 5.

NOTE : Do not add WOOD SCREWS ( F ) until STEP 5 .

**re- tighten the leg bolts after using a period of time**

To avoid wobbly product and gaps between legs and stretchers, please follow below steps to assemble:


- 1) Attach the legs. Do not completely tighten the bolts that hold the legs.
- 2) Attached the stretchers. Completely tighten the screws that hold the stretchers.
- 3) Set the chair on the floor to level and then finish tightening the leg bolts

# UTTERMOST

## ASSEMBLY INSTRUCTIONS


ITEM:23884

### STEP 3




NOTE : Leave BOLTS loose by 1/4 turn when securing LEGS until after STEP 5.

### STEP 4




NOTE : Do not add WOOD SCREWS ( F ) until STEP 5 .

**STEP 5** Using a PHILLIPS HEAD SCREW DRIVER and Wood SCREW ( F ) tighten all Stretchers securely . DO NOT OVERTIGHTEN .



### STEP 6



**re- tighten the leg bolts after using a period of time**

To avoid wobbly product and gaps between legs and stretchers, please follow below steps to assemble:

- 1) Attach the legs. Do not completely tighten the bolts that hold the legs.
- 2) Attached the stretchers. Completely tighten the screws that hold the stretchers.
- 3) Set the chair on the floor to level and then finish tightening the leg bolts