

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF **POWER BEFORE** INSTALLING OR SERVICING THIS FIXTURE.

## Installation Steps

- Carefully unpack your new fixture and lay out all the parts on a clear surface.
- Thread Hex nut-2 onto the Nipple-1, place the Washer over the end of Nipple-1, thread Nipple-1 through Mounting bar and secure with Hex nut-1 continuously until tight.
- Thread the Ground screw into the hole near the two dimples of the Mounting bar. Secure the Mounting bar to the outlet box with the Outlet box screws.
- Thread the Loop onto the Nipple-2.
- Weave the Fixture Wire and the Ground Wire through the Chain links. Open Key link-2, connect Loop to one end link of the Chain and close the Key link-2.
- Thread the Fixture Wire and ground wire through the Collar ring, Canopy, Nipple-1 and Mounting bar in order.
- Secure the Collar ring to the Nipple-1, Open Key link-1, connect Collar ring to the other one link of Chain and close the Key link-1.
- Make Wire connections with Wire Connector:
  - The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
  - Attach the Ground Wire and house ground wire to the Mounting bar with **the** green Ground Screw.
  - Carefully tuck wires back into the Outlet Box.
- Attach the Canopy to the Mounting bar by inserting the Collar ring, and then secure with the collar ring.
- Place the Glass shade, Cup onto the Socket, and secure with the Socket ring.
- Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
- Turn on the power at fuse or Circuit Box.

