



UTTERMOST

## ASSEMBLY AND INSTALLATION INSTRUCTIONS

21174

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

### Installation Steps

- Carefully unpack your new fixture and lay out all the parts on a clear surface.
- Spread the Arms so that the Arms are equal distance from each other.
- Thread Tube over Nipple-2, make sure place Ball glasses-1, Plastic washer, Iron washer to Tube carefully, screw Loop to Tube.
- Thread Finial over Nipple-3, hook Ball glasses-2 over ring of Finial and Arms.
- Thread Hex nut-2 onto the Nipple-1, place the Washer over the end of Nipple-1, thread Nipple-1 through Mounting bar and secure with Hex nut-1 continue until tight.
- Thread the Ground screw into the hole near the two dimples of the Mounting bar. Secure the Mounting bar to the outlet box with the Outlet box screws.
- Weave the Fixture Wire and the Ground Wire through the Chain links. Open Key link-2, connect Loop to one end link of the Chain and close the Key link-2.
- Thread the Fixture Wire and ground wire through the Collar ring, Canopy, Nipple-1 and Mounting bar in order.
- Secure the Collar ring to the Nipple-1, Open Key link-1, connect Collar ring to the other one link of Chain and close the Key link-1.
- Make Wire connections with Wire Connector:
  - The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
  - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground Screw.
 Carefully tuck wires back into the Outlet Box.
- Attach the Canopy to the Mounting bar by inserting the Collar ring, and then secure with the collar ring.
- Install the Light bulbs over the Socket in accordance with the fixture's specifications.  
**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
- Turn on the power at fuse or Circuit Box.



