

ASSEMBLY AND INSTALLATION INSTRUCTIONS

22249

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
2. Thread Mounting screws into the match holes in the Mounting bar.
3. Attach Mounting bar to Outlet box using Outlet box screws, tighten screws securely with screwdriver.
4. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground Screw.
 - Carefully tuck wires back into the Outlet Box.
5. After wires are connected, tuck them carefully inside outlet box. Raise fixture Canopy over two Mounting screws so they protrude through the holes in the Canopy, tighten screws securely with screwdriver.
6. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
7. Thread Hex nut-1 onto Nipple, and secure with Coupling. Slide Tube, Glass, Washer over Nipple, and secure with Hex nut-2. Place Decorative cap, and secure with Finial.
8. Hook Ball glass to Finial.
9. Turn on the power at fuse or Circuit Box.

