

ASSEMBLY AND INSTALLATION

INSTRUCTIONS

21861

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
2. Choose the suitable number of stems and install the Stem-1, Stem-2, Stem-3, Stem-4 into Nipple and Coupling.
3. Thread Mounting screws into the matching holes of Mounting bar, and tighten with Hex nut. Thread Ground screw into the hole of Mounting bar. Secure Mounting bar to outlet box with Outlet box screws.
4. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground Screw.
 - Carefully tuck wires back into the Outlet Box.
5. Place fixture Canopy over two Mounting screws so they protrude through the holes in Canopy. Thread Ball nuts onto Mounting screws and continue turning until fixture is snug against the wall.
6. Place Glass, Cup onto Socket, and secure with Socket ring using Wrench.
7. Install the light bulb in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
8. Turn on the power at fuse or Circuit Box.

