

REVELATION

by UTTERMOST

ASSEMBLY INSTRUCTIONS

R21564

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF WHILE POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

We suggest a licensed professional electrician for installation

Installation Steps

1. Turn power off at fuse or circuit box before starting installation process.
2. Carefully unpack your new fixture and lay out all the parts on a clear surface.
3. Thread the Hex nut-1 onto the Nipple-1, insert Lock washer over the end of Nipple-1, thread the Nipple-1 into the Mounting bar and secure with the Hex nut-1 continue until tight.
4. Thread the Hex nut-2 and Screw collar onto the bottom of the Nipple-1, then secure with the Hex nut-2.
5. Thread the Swivel (or Nipple-2) into the Screw collar.
6. Choose the suitable number of stems and install the Stem-1, Stem-2 into the Coupling. Remove excess wire.
7. Slip Collar ring and Canopy over the Stem assembly.
8. Slip Mounting bar assembly along wire and thread it into the Stem-1.
9. Raise fixture up and attach Mounting bar to the Outlet box using two Outlet box screws.
10. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.
- Carefully tuck wires back into the Outlet Box.
11. Slip Canopy up along stems and over the Mounting bar and hold it in position. Slip Collar ring up to Canopy and thread it onto the Screw collar, to secure Canopy.
12. Install four Decorative glass tubes A at the top and bottom of the Light cluster onto the Tubes respectively. Install the Decorative glass tubes B onto the other Tubes.
13. Install Decorative irons C onto the all Screws.
14. Install the light bulbs (Not Supplied) in accordance with the fixture's specifications.

DO NOT EXCEED THE MAXIMUM WATTAGE RATING!

