REVELATION
ASSEMBLY INSTRUCTIONS

ASSEMBLY AND INSTALLATION INSTRUCTIONS

R21572

WARNING:	TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Carefully unpack all lamp parts from carton. We suggest a licensed electrician for all fixture installations.

Installation Steps

1. **WARNING: BEFORE INSTALLING,** make sure the electricity supply is shut off to avoid a possible electric shock.

2. Carefully unpack your new fixture and lay out all the parts on a clear surface.

3. Choose the suitable number of stems and install the Stem-1, Stem-2, Stem-3, Stem-4 into the Coupling, as needed for your install. Remove excess wire if needed, leaving enough for installation.

4. Thread the Mounting screws into the matching holes of the Mounting bar, and tighten with the Hex nut. Thread the Ground screw into the hole of the Mounting bar. Secure the Mounting bar to the outlet box with the Outlet box screws.

5. Make Wire connections with Wire Connector:
   ---The smooth wire (w/ marking) from fixture to Black Wire from power source.
   ---The ribbed wire (w/o marking) from Fixture to White Wire from power source.
   ---Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.
   Carefully tuck wires back into the Outlet Box.

6. Place the fixture Canopy over the two Mounting screws so they protrude through the holes in the Canopy. Thread the Ball nut onto the Mounting screws and continue turning until the fixture is snug against the ceiling.

7. Install the light bulb (Not Supplied) in accordance with the fixture's specifications.
   DO NOT EXCEED THE MAXIMUM WATTAGE RATING!

SUPPLY GROUND WIRE
WHITE SUPPLY WIRE
MOUNTING SCREW
WHITE FIXTURE WIRE
GREEN GROUND SCREW
FIXTURE GROUND WIRE
CANOPY
OUTLET BOX
BLACK SUPPLY WIRE
WIRE CONNECT
BLACK FIXTURE WIRE
MOUNTING BAR
OUTLET BOX SCREW
HEX NUT